

A large, stylized letter 'A' is formed using the characters 'S' and 'Y'. The 'S' characters are arranged in a grid-like pattern to form the left and right sides of the letter, while 'Y' characters form the central vertical stem and the diagonal crossbars. The overall shape is a bold, blocky 'A' that fills most of the page.

[illegible]

(1) 68  
(1) 124  
(1) 158

EXESSETPRA - SET POWER FAIL AST ROUTINE ADDRESS  
EXESPOWERAST - INITIATE POWER FAIL AST FOR ALL INTERESTED PROCESSES  
PROCAST - SPECIAL KERNEL AST FOR POWERFAIL



```
0000 1 .TITLE SYSSETPRA - SET POWER FAIL AST SYSTEM SERVICE
0000 2 .IDENT 'V04-000'
0000 3
0000 4 *****
0000 5
0000 6 * COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
0000 7 * DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
0000 8 * ALL RIGHTS RESERVED.
0000 9
0000 10 * THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
0000 11 * ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
0000 12 * INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
0000 13 * COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
0000 14 * OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
0000 15 * TRANSFERRED.
0000 16
0000 17 * THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
0000 18 * AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
0000 19 * CORPORATION.
0000 20
0000 21 * DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
0000 22 * SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
0000 23
0000 24 *****
0000 25
0000 26
0000 27 ++
0000 28
0000 29 Facility:
0000 30
0000 31 Abstract: SYSSETPRA IMPLEMENTS THE $SETPRA SYSTEM SERVICE WHICH ENABLES
0000 32 A PROCESS TO RECEIVE AN AST WHEN POWER IS RESTORED AFTER A
0000 33 SUCCESSFUL POWER RECOVERY.
0000 34
0000 35 Environment:
0000 36
0000 37 Author: RICHARD I. HUSTVEDT, Creation date: 18-JUN-1978
0000 38
0000 39 Modified by:
0000 40
0000 41 Version .
0000 42 of -
0000 43 --
0000 44
0000 45
0000 46 Include files:
0000 47
0000 48 $ACBDEF ; DEFINE ACB OFFSETS
0000 49 $PCBDEF ; DEFINE PCB OFFSETS
0000 50 $$$DEF ; DEFINE SYSTEM SERVICE STATUS CODES
0000 51
0000 52
0000 53 MACROS:
0000 54
0000 55
0000 56
0000 57 Equated Symbols:
```

```
00000004 0000 58 ;
00000008 0000 59 ; ASTADR = 4
00000008 0000 60 ; ACMODE = 8 ; ARGUMENT LIST OFFSET TO AST ADDRESS
00000008 0000 61 ; ; ARGUMENT LIST OFFSET TO ACCESS MODE
00000008 0000 62 ;
00000008 0000 63 ;
00000008 0000 64 ; Dwn Storage:
00000008 0000 65 ;
00000000 0000 66 ; .PSECT Y$EXEPAGED ; PAGED CODE
```

SYS  
VA)  
43  
The  
18  
20  
  
Mac  
--  
\$2  
- \$2  
TOT  
  
969  
The  
MAC



```
0000 68 .SBTTL EXESSETPRA - SET POWER FAIL AST ROUTINE ADDRESS
0000 69 :++
0000 70 : Functional Description:
0000 71 : EXESSETPRA IMPLEMENTS THE SYSTEM SERVICE $SETPRA WHICH ENABLES A
0000 72 : PROCESS TO REQUEST AN AST AFTER THE RESTORATION OF POWER FOLLOWING
0000 73 : A POWER FAILURE. THE AST ROUTINE IS ENTERED WITH A PARAMETER
0000 74 : GIVING THE DURATION OF THE POWER OUTAGE IN .01 SECOND UNITS.
0000 75 : THIS IS A SINGLE SHOT AST AND MUST BE RE-ENABLED EACH TIME IT OCCURS.
0000 76 : IT IS AUTOMATICALLY CANCELED AT IMAGE RUNDOWN.
0000 77 :
0000 78 : Calling Sequence:
0000 79 : CALLG  ARGLIST,EXESSETPRA
0000 80 :
0000 81 : Input Parameters:
0000 82 :   ASTADR(AP) - ADDRESS OF AST ROUTINE
0000 83 :   ACMODE(AP) - ACCESS MODE, MAXIMIZED WITH THAT OF CALLER
0000 84 :
0000 85 : Implicit Inputs:
0000 86 :   PCB OF CURRENT PROCESS LOCATED VIA SCH$GL_CURPCB
0000 87 :
0000 88 : Output Parameters:
0000 89 :   R0 - COMPLETION STATUS CODE
0000 90 :
0000 91 : Implicit Outputs:
0000 92 :   NONE
0000 93 :
0000 94 : Side Effects:
0000 95 :   NONE
0000 96 :
0000 97 : Status Codes:
0000 98 :   $$$_NORMAL - NORMAL, SUCCESSFUL COMPLETION
0000 99 :   $$$_EXQUOTA - AST QUOTA EXCEEDED
0000 100 :
0000 101 :--
0000 102 :.LIST  MEB ; Show macro expansions
0000 103 :
50 08 AC 02 00 003C 0000 104 :.ENTRY  EXESSETPRA,*M<R2,R3,R4,R5> ;
0000 105 :EXTZV  #0,#2,ACMODE(AP),R0 ; GET ACCESS MODE ARGUMENT
51 00000000'EF 9E 0008 106 :BSBW  EX$MAXACMODE ; MAXIMIZE WITH THAT OF CALLER
0000 107 :MOVAB  CTL$GL_POWERAST,R1 ; GET ADDRESS OF POWER FAIL AST POINTER
0000 108 :TSTL  (R1) ; IS THERE ONE CURRENTLY?
0000 109 :BNEQ  10$ ; YES, SKIP QUOTA BUSINESS
0000 110 :TSTW  PCB$W_ASTCNT(R4) ; CHECK FOR AST QUOTA
0000 111 :BLEQ  EXQUOTA ; ERROR EXIT IF NO QUOTA
0000 112 :DECW  PCB$W_ASTCNT(R4) ; ONE LESS FOR AST QUOTA
0000 113 10$: MOVL  ASTADR(AP),(R1) ; SET ADDRESS OF AST ROUTINE
0000 114 :MOVB  R0,<CTL$GB_PWRMODE-CTL$GL_POWERAST>(R1) ; AND ACCESS MODE FOR AST
0000 115 :BBSS  #PCB$V_PWRAST,PCB$V_STS(R4),20$ ; SET POWER AST FLAG FOR PROCESS
0000 116 20$: MOVZWL #$$$_NORMAL,R0 ; RETURN NORMAL SUCCESSFUL COMPLETION
0000 117 :RET ;
0000 118 :
0000 119 EXQUOTA: ; EXCEEDED AST QUOTA
0000 120 :MOVZWL #$$$_EXQUOTA,R0 ; SET STATUS CODE FOR QUOTA EXCEEDED
0000 121 :RET ; AND RETURN
0000 122 :
```

50 08 AC 02 00 003C 0000 104 :.ENTRY EXESSETPRA,\*M<R2,R3,R4,R5> ;

51 00000000'EF 9E 0008 106 :BSBW EX\$MAXACMODE ; MAXIMIZE WITH THAT OF CALLER

0000 107 :MOVAB CTL\$GL\_POWERAST,R1 ; GET ADDRESS OF POWER FAIL AST POINTER

0000 108 :TSTL (R1) ; IS THERE ONE CURRENTLY?

0000 109 :BNEQ 10\$ ; YES, SKIP QUOTA BUSINESS

0000 110 :TSTW PCB\$W\_ASTCNT(R4) ; CHECK FOR AST QUOTA

0000 111 :BLEQ EXQUOTA ; ERROR EXIT IF NO QUOTA

0000 112 :DECW PCB\$W\_ASTCNT(R4) ; ONE LESS FOR AST QUOTA

0000 113 10\$: MOVL ASTADR(AP),(R1) ; SET ADDRESS OF AST ROUTINE

0000 114 :MOVB R0,<CTL\$GB\_PWRMODE-CTL\$GL\_POWERAST>(R1) ; AND ACCESS MODE FOR AST

0000 115 :BBSS #PCB\$V\_PWRAST,PCB\$V\_STS(R4),20\$ ; SET POWER AST FLAG FOR PROCESS

0000 116 20\$: MOVZWL #\$\$\$\_NORMAL,R0 ; RETURN NORMAL SUCCESSFUL COMPLETION

0000 117 :RET ;

0000 118 :

0000 119 EXQUOTA: ; EXCEEDED AST QUOTA

0000 120 :MOVZWL #\$\$\$\_EXQUOTA,R0 ; SET STATUS CODE FOR QUOTA EXCEEDED

0000 121 :RET ; AND RETURN

0000 122 :

```
0034 124 .SBTTL EXESPOWERAST - INITIATE POWER FAIL AST FOR ALL INTERESTED PROCESSES
0034 125 :++
0034 126 : Functional Description:
0034 127 : EXESPOWERAST IS CALLED BY THE SWAPPER AFTER A POWER RECOVERY TO
0034 128 : SEND A SPECIAL KERNEL MODE AST TO EACH PROCESS WHICH HAS ENABLED
0034 129 : POWER FAIL ASTS.
0034 130 :
0034 131 : Calling sequence:
0034 132 : JSB EXESPOWERAST
0034 133 :
0034 134 :--
0034 135 EXESPOWERAST::
0034 136 PUSH R4,R5,R6 : SAVE NON-VOLATILE REGISTERS
56 00000000'EF BB 0038 137 MOVL SCH$GL_MAXPIX,R6 : SET STARTING PROCESS INDEX FOR SCAN
003F 138 PCBLOOP:
54 00000000'FF46 D0 003F 139 MOVL @SCH$GL_PCBVEC[R6],R4 : GET A PCB ADDRESS
30 24 A4 16 E1 0047 140 BBC #PCB$V_PWRAST,PCB$S_STS(R4),NEXTPCB : BRANCH IF NO AST FOR THIS PROC
00000000'EF 16 004C 141 JSB EXESALCOCIRP : ALLOCATE AN I/O PACKET
27 50 E9 0052 142 BLBC R0,NEXTPCB : SKIP IF ERROR
00 24 A4 16 E5 0055 143 BBCC #PCB$V_PWRAST,PCB$S_STS(R4),10$ : CLEAR AST FLAG
55 52 D0 005A 144 10$: MOVL R2,R5 : MOVE BASE TO ACB BASE REGISTER
0B A5 C0 8F 90 005D 145 MOVB #<<1@ACB$V_QUOTA>!<1@ACB$V_KAST>>,ACB$B_RMOD(R5) : SET AS SPECIAL AS
0C A5 60 A4 D0 0062 146 MOVL PCB$S_PID(R4),ACB$S_PID(R5) : SET PID FOR AST
18 A5 8A AF 9E 0067 147 MOVAB B*PROCAST,ACB$S_KAST(R5) : SET ADDRESS FO SPECIAL AST
14 A5 00000000'EF D0 006C 148 MOVL EXESGL_PFASTIM,ACB$S_ASTPRM(R5) : SET AST PARAMETER
52 D4 0074 149 CLRL R2 : NULL PRIORITY INCREMENT
00000000'EF 16 0076 150 JSB SCH$QAST : ENQUEUE AST FOR PROCESS
007C 151 NEXTPCB:
C0 56 F4 007C 152 SOBGEQ R6,PCBLOOP : CONTINUE FOR ALL PIX VALUES
00000000'EF D4 007F 153 CLRL EXESGL_PFASTIM : CLEAR DURATION OF POWERFAIL
0070 8F BA 0085 154 POPR #^M<R4,R5,R6> : RESTORE REGISTERS
05 0089 155 RSB : AND RETURN
008A 156
```

```
008A 158 .SBTTL PROCAST - SPECIAL KERNEL AST FOR POWERFAIL
008A 159 ;++
008A 160 ; Functional Description:
008A 161 ; PROCAST RUNS AS A SPECIAL KERNEL AST IN THE CONTEXT OF THE PROCESS
008A 162 ; WHERE IT CAN ACCESS THE ADDRESS OF THE POWER FAIL AST ROUTINE AND
008A 163 ; REQUEUE THE AST AT THE PROPER ACCESS MODE.
008A 164 ;
008A 165 ;--
008A 166 PROCAST:
51 00000000'EF 9E 008A 167 MOVAB CTL$GL_POWERAST,R1 ; GET ADDRESS OF POWER FAIL AST POINTER
10 A5 61 D0 0091 168 MOVL (R1),ACB$AST(R5) ; SET CORRECT AST ROUTINE ADDRESS
0B A5 0000'C1 88 0095 169 BISB <CTL$GB_PWRMODE-CTL$GL_POWERAST>(R1),ACB$B_RMOD(R5) ;
009B 170 ; SET CORRECT ACCESS MODE
61 D4 009B 171 CLRL (R1) ; ZAP AST POINTER
52 D4 009D 172 CLRL R2 ; SET NULL PRIORITY INCREMENT
00000000'EF 17 009F 173 JMP SCH$QAST ; QUEUE NORMAL AST
00A5 174
00A5 175 .END
```



SYSSETPRA  
Symbol table

- SET POWER FAIL AST SYSTEM SERVICE <sup>1</sup> 7

16-SEP-1984 02:32:49 VAX/VMS Macro V04-00  
5-SEP-1984 03:57:15 [SYS.SRC]SYSSETPRA.MAR;1

Page 6  
(1)

ACBSB_RMOD	= 0000000B		
ACBSL_AST	= 00000010		
ACBSL_ASTPRM	= 00000014		
ACBSL_KAST	= 00000018		
ACBSL_PID	= 0000000C		
ACBSV_KAST	= 00000007		
ACBSV_QUOTA	= 00000006		
ACMODE	= 00000008		
ASTADR	= 00000004		
CTL\$GB_PWRMODE	*****	X	02
CTL\$GL_POWERAST	*****	X	02
EX\$ALCOCIRP	*****	X	02
EX\$GL_PFATIM	*****	X	02
EX\$MAXACMODE	*****	X	02
EX\$POWERAST	00000034	RG	02
EX\$SETPRA	00000000	RG	02
EXQUOTA	00000030	R	02
NEXTPCB	0000007C	R	02
PCBSL_PID	= 00000060		
PCBSL_STS	= 00000024		
PCBSV_PWRAS1	= 00000016		
PCBSW_ASTCNT	= 00000038		
PCBLOOP	0000003F	R	02
PROCAST	0000008A	R	02
SCH\$GL_MAXPIX	*****	X	02
SCH\$GL_PCBVEC	*****	X	02
SCH\$QAST	*****	X	02
SS\$EXQUOTA	= 0000001C		
SS\$NORMAL	= 00000001		

-----  
! Psect synopsis !  
-----

PSECT name	Allocation	PSECT No.	Attributes													
. ABS .	00000000 ( 0.)	00 ( 0.)	NOPIC	USR	CON	ABS	LCL	NOSHR	NOEXE	NORD	NOWRT	NOVEC	BYTE			
\$ABSS	00000000 ( 0.)	01 ( 1.)	NOPIC	USR	CON	ABS	LCL	NOSHR	EXE	RD	WRT	NOVEC	BYTE			
Y\$EXEPAGED	000000A5 ( 165.)	02 ( 2.)	NOPIC	USR	CON	REL	LCL	NOSHR	EXE	RD	WRT	NOVEC	BYTE			

-----  
! Performance indicators !  
-----

Phase	Page faults	CPU Time	Elapsed Time
Initialization	29	00:00:00.07	00:00:00.33
Command processing	106	00:00:00.57	00:00:02.05
Pass 1	227	00:00:05.23	00:00:12.15
Symbol table sort	0	00:00:00.85	00:00:02.28
Pass 2	50	00:00:01.02	00:00:02.13
Symbol table output	5	00:00:00.04	00:00:00.05
Psect synopsis output	2	00:00:00.02	00:00:00.02
Cross-reference output	0	00:00:00.00	00:00:00.00
Assembler run totals	421	00:00:07.80	00:00:19.01

The working set limit was 1200 pages.

28491 bytes (56 pages) of virtual memory were used to buffer the intermediate code.  
There were 30 pages of symbol table space allocated to hold 577 non-local and 3 local symbols.  
175 source lines were read in Pass 1, producing 16 object records in Pass 2.  
10 pages of virtual memory were used to define 9 macros.

-----  
! Macro library statistics !  
-----

Macro library name	Macros defined
-----	-----
\$255\$DUA28:[SYS.OBJ]LIB.MLB;1	2
\$255\$DUA28:[SYS.LIB]STARLET.MLB;2	4
TOTALS (all libraries)	6

631 GETS were required to define 6 macros.

There were no errors, warnings or information messages.

MACRO/LIS=LIS\$:SYSSETPRA/OBJ=OBJ\$:SYSSETPRA MSRC\$:SYSSETPRA/UPDATE=(ENH\$:SYSSETPRA)+EXECMLS/LIB



0388

DIGITAL EQUIPMENT CORPORATION  
CONFIDENTIAL AND PROPRIETARY